
























**Versatile spray accessories make your hot cleaner
to all-rounder
parts cleaning**






<p>•Material Number Standard •Material Number in stainless steel</p>	<p>Description</p>	<p>Picture</p>
<p>SR-BS-A ESR-BS-A</p>	<p>Option Spray gun with quick change coupling device, 2 m hose with heat protection and plug nipple. Standard jet pipe will not be included, if this option is chosen. In stainless steel version fix mounted, without nipple</p>	
<p>SR-BS ESR-BS</p>	<p>Retrofit Kit: Spray gun with quick change coupling device, 2 m hose with heat protection and plug nipple. In stainless steel version fix mounted, without nipple</p>	
<p>SR-AD</p>	<p>Adapter from hand screw connection to quick change coupling</p>	
<p>SR-ST ESR-ST</p>	<p>Standard – jet pipe</p>	
<p>SR-IR ESR-IR</p>	<p>slim nozzle for cleaning into holes</p>	
<p>SR-HO ESR-HO</p>	<p>Nozzle with 120° angle for cleaning into tubes</p>	

<p>•Material Number Standard</p> <p>•Material Number in high-grade steel</p>	<p>Description</p>	<p>Picture</p>
<p>SR-SL</p> <p>ESR-SL</p>	<p>rigid, thin blind hole nozzle , Ø 4 mm</p>	
<p>SR-ES</p> <p>ESR-ES</p>	<p>rigid, thin blind hole nozzle , also for cleaning electrostatic filter elements Ø 5 mm, 4 x 90° angle</p>	
<p>SR-FX</p> <p>ESR-FX</p>	<p>flexible nozzle for holes and tubes</p>	
<p>SR-PT</p> <p>ESR-PT</p>	<p>Nozzle with 0° angle for very stubborn pollutions</p>	
<p>SR-PI</p> <p>ESR-PI</p>	<p>Synthetic brush</p>	
<p>SR-PI E</p> <p>ESR-PI E</p>	<p>Stainless steel brush</p>	
<p>SR-BA</p>	<p>Adapter für Mink brushes in variable configuration</p>	

<p>•Material Number Standard</p> <p>•Material Number in high-grade steel</p>	<p>Description</p>	<p>Picture</p>	
<p>SR-TB</p>	<p>Brush plate Mink d=45mm incl. adapter</p>		
<p>SR-FA</p> <p>ESR-FA</p>	<p>Changeable insert with high water performance for surfaces. Reduced pressure and temperature.</p>		
<p>SR-ND</p> <p>ESR-ND</p>	<p>needle jet with outer diameter 2,5mm for small holes and blind holes, with protective cap; from 4 bar</p>		
<p>SR-RT</p>	<p>Rotary table diameter 300 mm in Aluminium, max load capacity 40 kg</p>		
<p>SR-AU N</p>	<p>Holder for changeable inserts in stainless steel</p>		
<p>SR-SM</p>	<p>protection mat for grid of the modell 1000 SR 900x600 mm in Vinyl</p>		
<p>SR-FU</p>	<p>Foot switches with 2 m hose and habile handle, operation via the foot switch, integrated in cleaning equipment</p> <p>Not available in stainless steel</p>		

**Versatile accessories make your hot cleaner
to all-rounder
machines and large part cleaning**

<p>•Material Number Standard •Material Number in high-grade steel</p>	<p>Description</p>	<p>Picture</p>
<p>Special nozzles - and executions on request!</p>		
<p>1000 SR-EA</p>	<p>Option external water supply... direct connection on a tap. Thus, the pressure would be increased by the pre – pressure of the water supply. Temperature range between 80 - 85°C; no direct metering of detergent possible</p>	
<p>SR-BSL-A ESR-BSL-A</p>	<p>Option spray gun for the lance with hand screw connection device, 5m hose and nipple. Standard lance will not be included, if this option is chosen. In stainless steel version fix mounted, without nipple</p>	
<p>SR-BSL ESR-BSL</p>	<p>Retrofit kit: spray gun for the lance with hand screw connection device, 5m hose and nipple. In stainless steel version fix mounted, without nipple</p>	

<p>•Material Number Standard</p> <p>•Material Number in high-grade steel</p>	<p>Description</p>	<p>Picture</p>
<p>SR-LA 600 SR-LA 900 SR-LA 1200</p> <p>ESR-LA 600 ESR-LA 900 ESR-LA 1200</p>	<p>Lance in length 600/900/1200 mm as a changeable insert with a power nozzle</p> <p>In stainless steel V2A</p>	
<p>SR-FA 600 SR-FA 900 SR-FA 1200</p> <p>ESR-FA 600 ESR-FA 900 ESR-FA 1200</p>	<p>Lance in length of 600/900/1200 mm as a changeable insert with a flat-jet nozzle asymmetric</p> <p>In stainless steel V2A</p>	
<p>SR-DL</p>	<p>For the series 1000 SR-DP, 1000 SRE-DP, 1000 ESE and 1000 ESR. By means of a valve an additional lance can be activated to have the double water capacity and cleaning performance.</p>	
<p>SR-DV</p>	<p>Pressure adjustment at the pistol</p>	
<p>SR-034E</p> <p>ESR-034E</p>	<p>5 m extension hose with coupling device</p>	

Special nozzles, lances and hoses on demand