



Technical Data Low pressure Hotwasher 1000 OSE

Universal spray cleaner, without collector, infinitely adjustable pressure, no metering device for cleaning agent concentrate, oil shortage control, overheat fuse among others for machine cleaning, which runs with oil up to a viscosity of 150 cSt.

Technical Data	1000 OSE
Working pressure	~ 3 – ca. 12 bar
Spray/water volume	~ 1,0 – 2,4 l/min
Operating temperature	max. 80°C in 60 sec, the temperature is restricted to max 80°C at the factory
Type of current	3P-N-PE/400V/50Hz
Nominal power consumption	10 KW
Filling quantities <ul style="list-style-type: none"> • oil tank • Concentrate tank 	60 liter n.a.
Main power cable	7,5 m
Spray hose lance	5 m
Spray hose pistol	option
Size (LxWxH)	98x55x67 cm
Weight empty	Approx. 65 kg
Sound level	<70 dBA
Pressure adjustment	yes
Garden connection	n.a.
Temperature adjustment	n.a.
Emptying of tank	Yes
Concentrate reservoir	n.a.
Changeable inserts	option
Water recycling	n.a.

technical modifications reserved. Version 07/2012

ph-cleantec GmbH, Gutenbergstraße 14, D 70736 Fellbach, www.ph-cleantec.com
Tel.: 0049 / (0)711/5180600, Fax: 0049 / (0)711/5180994, e-mail: info@ph-cleantec.com