

Technical data



universal low pressure hot cleaning machine **SRK**



Mobile, made in a compact construction, without a tank. It is possible to suck in liquids from a separate container. Pressure performance ca. 4.5 bar at 60°C operating temperature. Application with single-phase alternating voltage.

<i>Technical Data</i>	<b>SRK</b>
Pressure performance	ca. 4.5 bar
Spray/water volume	~ 1.0 l/min
Operating temperature	~ 60°C
Type of current	1P-N-PE/230V/50Hz
Nominal power consumption	3 KW
Connection cable	7.5 m
Sprinkler hose lance	5 m
Gun with quick-change coupling	Standard with 600 mm lance
Dimensions (LxWxH)	530x250x800 mm
Water supply	Suction from sep. container
Weight (net)	ca. 25 kg
Filtering	n.a.
Acoustic level	<70 dB (A)
Pressure adjustment	n.a.
Garden connection	•
Temperature adjustment	n.a.
Separate ventilation circulation	n.a.
Dosing of cleaning agent	n.a.
Interchangeable insert	Option
Suction hose	3 m

Subject to technical modifications. Status as of 04/2016

ph-cleantec GmbH, Gutenbergstraße 14, 70736 Fellbach, [www.ph-cleantec.com](http://www.ph-cleantec.com)  
Tel.: +49 (0)711/5180600, Fax: +49 (0)711/5180994, e-mail: info@ph-cleantec.com