



Technical data sheet Low pressure hot water cleaner type 1000 SRK-AS resp. EA

Mobile, compact design without tank. The unit permits either to suck the liquid directly from large-sized tanks or tool machines, or can be connected with an external water tap (pre - pressure).

The model **1000 SRK-AS-EA** combine the two variants. The change between the suction and external supply happens via a three-way valve

Min. pre-pressure 3 bar, max. 6 bar. At pressure ranges (total pressure) higher than 8 bar, the heater performance is restricted.

Technical data	1000 SRK-EA	1000 SRK-AS
Working pressure	approx. 3-8 bar + pre-pressure	approx. 3-7,5 bar
Spray/water volume	1,0 – 1,8 l/min	1,0 – 1,8 l/min
Operating temperature	95 °C in 60 sec	95 °C in 60 sec
Type of current	3P-N-PE/400V/50Hz, 16 A	3P-N-PE/400V/50Hz, 16 A
Nominal power consumption	10 KW	10 KW
Main power cable	5 m	5 m
Hose lance	5 m	5 m
Pistol with quick change coupling device .	Standard with 600 mm lance	Standard with 600 mm lance
Size (HxWxD)	92x48x45 cm	92x48x45 cm
Water supply	External Connection (pre-pressure)	Suction process
Weight	approx. 48 kg	approx. 55 kg
Filtration	n.a.	25 µm
Noise level	<70 dBA	<70 dBA
Pressure adjustment	•	•
Garden connection	•	n.a,
Temperature adjustment	Option	Option
Special deairing process	n.a.	•
Dosing of cleaning agent	Option metering pump.	n.a.
Exchangeable inserts	Option	Option
Suction hose	n.a.	5 m

Technical modifications reserved.