



Technical data Universal low pressure cleaner 1000 SR

Mobile universal spray cleaner with cleaning bath for parts, solid drip-off grid, spraying device, with 2 quickly exchangeable hoses, automatic pressure adjustment, metering device for cleaning agent concentrate to speed up cleaning process, fully automatic water-recycling system, with slosh baffle, water shortage control, overheat fuse

Technical data	1000 SR
Adjustable operating pressure	approx. 3 – 7,5 bar
Spray/water flow rate	~ 1,1 – 1,8 l/min
Operating temperature	~ 95 °C in 60 sec.
Type of current	3P-N-PE/400V/50 cps
Nominal power consumption	10,0 KW
Capacity <ul style="list-style-type: none"> • Fresh water tank • Detergent tank • Bath 	60 liter 5 liter 30 liter
Connecting cable	7,5 m
Spray hose lance	5 m
Spray hose pistol	3 m
Dimensions (LxWxH)	109 x 73 x 118 cm
Dimensions of cleaning grid (LxW)	90x60 cm
Weight (empty)	approx. 100 kg
Water recycling	yes
Load capacity of collector	Approx. 80 kg
Noise level	<70 dBA
Adjustable pressure	yes
GEKA connection	yes
Temperature adjustment	option
Tank emptying	yes
Concentrate reservoir	yes
Changeable inserts	option

Technical modifications reserved.